

CELLULOSE EXTRACTION THIMBLES

for Soxhlet extraction

Grade 30

extraction thimbles made of cellulose, are perfect sample reservoirs for Soxhlet extraction in quality control, research and/or analysis. Solvent extraction from solids and semi-solids can be carried out easily and reliably. The thimbles fit Soxhlet extractors and automatic extractors.

Material	Cellulose
Shape	hollow cylinders with round bottom
Max. Temp. Res.:	120 °C

ID x H	Code	Grade/Description	Pack of
22 x 80 mm ^{1.}	FTR 1201.022080	30/extraction thimbles	25
25 x 80 mm	FTR 1201.025080	30/extraction thimbles	25
25 x 100 mm ^{1.}	FTR 1201.025100	30/extraction thimbles	25
26 x 60 mm ^{3.}	FTR 1201.026060	30/extraction thimbles	25
30 x 80 mm	FTR 1201.030080	30/extraction thimbles	25
33 x 80 mm ^{2.,3.,4.}	FTR 1201.033080	30/extraction thimbles	25
33 x 94 mm ^{1.}	FTR 1201.033094	30/extraction thimbles	25
33 x 118 mm	FTR 1201.033118	30/extraction thimbles	25
43 x 123 mm ^{1.}	FTR 1201.043123	30/extraction thimbles	25

1. fits Büchi B-811
2. fits Gerhardt Soxterm Automatic
3. fits Foss Tecator Soxtec System
4. fits Velp Extractors SER 148



GRIDDED MEMBRANE FILTERS

Sartorius® brand

Sterile, individually packed membrane filters have long become standard for routine microbiological quality control because of the user benefits they offer. They are ready-to-use and save preparatory time, they avoid the possibility of contamination of remaining filters in opened packs and are GLP conform, having filter identification and lot number printed on each individual envelope.

Material	cellulose nitrate, white with black grid
Grid size	3,1 x 3.1 mm
Pore size	0,45 micron
Diameter	47 mm
Presentation	sterile, individually packed

Diam.	Code	Pack of
47 mm	SAR 11406-47ACN	100

